

A VERSATILE RANGE OF TOP QUALITY CLOTHS

This label warrants your quality

A UNIQUE LABEL

Fibercon sailcloth is woven with our exclusive Fibercon high tenacity yarn.

WHY DO WE SPIN OUR OWN POLYESTER HIGH TENACITY YARN?

The production of polyester fibers has increasingly been outsourced to low cost countries where spinning companies no longer produce fibers to the quality and specifications necessary for weaving superior sailcloth. The trading name of these fibers has remained the same but the actual performance of the fibers has degraded dramatically. As the leader in premium woven sailcloth, Contender has always realised that the fiber used in our cloth is as important as the weave and finish. We have always been in control of the weave and finish and now we have taken control over the quality of the fiber as well.

HIGH TENACITY YARN

High tenacity means high breaking strength and low stretch.

UV RESISTANT YARN

UV radiation from sunlight can break down polyester fibers. We added UV blockers to the Fibercon polymer so when you select Fibercon sailcloth you are getting the highest UV resistance available in any sailcloth.

FIBERCON YARN AVAILABLE IN A WIDE RANGE OF SIZES

The selection of fibers for their size is an important aspect of determining the sailcloth's properties relative to weight and balance. Fibercon fibers are spun in a wide range of sizes engineered to construct a complete series of premium styles.



Woven in different countries of the European Union, finished at Contender Finishing GmbH





• Designed for cross-cut sails from 28 to 52 feet

Developed for the yachtsman that seeks increased performance and need greater load bearing strength from their woven sails. This cloth combines the high-quality features of Fibercon® yarns with the immense tensile strength and flexibility of additional Vectran yarns.

The finishing of our Fibercon® fabrics is geared to your cruising needs or racing aspirations. Every production process is carefully overseen so that you receive a consistent quality of sail.



We recommend a firm Polypreg finish for our Fibercon® Pro Vectran cloth. The firm Polypreg finish is optimised for the increased diagonal stability needed in more performance oriented sails.

APPLICATIONS FIBERCON® PRO VECTRAN

BOAT LENGTH	MAINSAIL		HEADSAIL
IN FT	MULTIHULL	MONOHULL	100% FURLING
± 28	7.7	6.7	6.7
± 32	8.7	7.7	7.7
± 36	9.7	7.7	7.7
± 40	11.7	8.7	8.7
± 44	11.7	8.7 / 9.7	9.7
± 48	2 × 7.7	9.7	9.7
± 52	2 x 7.7	11.7	11.7